ULTRIX

digital

Guide to VAX C for ULTRIX

Order Number: AA-ME83B-TE

Guide to VAX C for ULTRIX ™

Order Number: AA-ME83B-TE

June 1990

This document describes VAX C constructs in context with both the history of the C programming language and that of the ULTRIX environment on VAX processors. It contains information on VAX C program development in the ULTRIX environment on VAX processor the VAX C programming language, and cross-system portability concerns.

Revision/Update Information: This manual supersedes the *Guide to VAX C for ULTRI.* (Order No. AA-KK18A-TE).

Operating System and Version: ULTRIX Version 4.0 or higher

digital equipment corporation
maynard, massachusetts

The information in this document is subject to change without notice and should not be construed as a commitment by Digital Equipment Corporation. Digital Equipment Corporation assumes no responsibility for any errors that may appear in this document.

The software described in this document is furnished under a license and may be used or copied only in accordance with the terms of such license.

No responsibility is assumed for the use or reliability of software on equipment that is not supplied by Digital Equipment Corporation or its affiliated companies.

The postpaid Reader's Comments forms at the end of this document request your critical evaluation to assist in preparing future documentation.

The following are trademarks of Digital Equipment Corporation:

ALL–IN–1	EduSystem	RT
DEC	IAS	ULTRIX
DEC/CMS	MASSBUS	UNIBUS
DEC/MMS	PDP	VAX
DECnet	PDT	VAXcluster
DECmate	P/OS	VMS
DECsystem–10	Professional	VT
DECSYSTEM–20	Q–bus	Work Processor
DECUS	Rainbow	
DECwriter	RSTS	digital™
DIBOL	RSX	

ZK4585

Contents

Developing VAX C Programs on ULTRIX

Chapter 2 Developing VAX C Programs for ULTRIX

Chapter 3 The dbx Debugger

VAX C Programming Concepts

Chapter 4 Program Structure

Figures

Tables

Preface

This guide provides reference information for using VAX C on ULTRIX ™ systems. It also contains information on how to develop and debug VAX C programs on the ULTRIX operating system running on VAX hardware. VAX C is not intended for use on RISC hardware.

Intended Audience

This guide is intended for experienced and novice programmers who need reference information on VAX C for ULTRIX systems.

Document Structure

This guide has ten chapters and four appendixes as follows:

Chapter 1 describes portability considerations for migrating C source programs between different compilers and the VMS and ULTRIX operating systems.

Chapter 2 explains how to create and compile and link VAX C programs. It also describes the forms of compiler output that you can select.

Chapter 3 discusses the debugging facilities provided by the dbx debugger and how to use the dbx commands.

Chapter 4 explains the structure of VAX C programs, including an introduction to the language, methods of controlling program flow, and the fundamental structures such as function definitions, keywords, blocks, and comments.

Chapter 5 describes the VAX C statements that provide flow control, conditional executions, looping, and interruption.

Chapter 6 discusses the expressions and operators available in VAX C, including unary, binary, conditional, comma, and assignment. Chapter 6 also explains the rules for data-type conversions.

Chapter 7 explains the data types and declarations that VAX C supports.

Chapter 8 describes the storage classes and allocation.

Chapter 9 explains the purposes and appropriate uses of the various VAX C preprocessor directives.

Chapter 10 explains the purposes and appropriate uses of the various VAX C predefined macros and builtin functions.

™ ULTRIX is a trademark of Digital Equipment Corporation.

Appendix A describes how to use the lk linker as a separate tool for linking, instead of using the **vcc** command, which both compiles and links programs.

Appendix B lists all the diagnostic messages produced by the **vcc** command program and the VAX C compiler.

Appendix C describes the mechanisms available to assist in transporting C programs between the VMS and ULTRIX operating systems.

Appendix D provides a summary of the **vcc** command and the language elements of VAX C.

Associated Documents

You may find the following documents useful when programming in VAX C. The last two documents are included if you want to transport VAX C programs between the ULTRIX and VMS operating systems.

- *The C Programming Language*[1] — Provides a more intensive tutorial than that found in the beginning of Chapter 4 of this guide.

  VAX C contains additional features and enhancements to the C language as it is defined in *The C Programming Language*. Therefore, use this guide as the reference for a full description of VAX C.

- *ULTRIX Documentation Set* — Provides information about the ULTRIX operating system and its utilities.

- *Guide to VAX C* — Provides tutorial information that describes using VAX C on the VMS operating system.

- *VMS Master Index* — Provides information on the VAX machine architecture in the VMS operating system environment. (This index identifies manuals that cover individual topics about using the VMS operating system.)

Conventions

Convention	Meaning
RETURN	The symbol RETURN represents a single stroke of the RETURN key on a terminal.
CTRL/X	The symbol CTRL/X, where letter X represents a terminal control character, is generated by holding down the CTRL key while pressing the key of the specified terminal character.
% cprog RETURN	In interactive examples, the user's response to a prompt is printed in red; system prompts are printed in black.

[1] Brian W. Kernighan and Dennis M. Ritchie, *The C Programming Language* (Englewood Cliffs, New Jersey: Prentice Hall, 1988).

Convention	Meaning
float x; . . . x = 5;	A vertical ellipsis indicates that not all of the text of a program or program output is shown. Only relevant material is shown in the example.
option, . . .	A horizontal ellipsis indicates that additional parameters, options, or values can be entered. A comma that precedes the ellipsis indicates that successive items must be separated by commas.
[output-source, . . .]	Square brackets, in function synopses and a few other contexts, indicate that a syntactic element is optional. Square brackets are not optional, however, when used to delimit the dimensions of a multidimensional array in VAX C source code.
sc-specifier ::= **auto** **static** **[extern]** **register**	In syntax definitions, items appearing separate lines are mutually exclusive alternatives.
[a | b]	Braces surrounding two or more items separated by a vertical bar (|) indicate a choice; you must choose one of the two syntactic elements.
Δ	A delta symbol is used in some contexts to indicate a single ASCII space character.
auto storage class **fprintf** function	Boldface type identifies language keywords and the names of independently compiled external functions.